

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
• PPE inspection should be conducted with the manufacturer's Instructions for Use.
Download the instructions at [PETZL.COM](https://www.petzl.com).



PULLEYS

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

<input checked="" type="radio"/> Good condition (G)	<input type="radio"/> To monitor (TM)	<input type="radio"/> To repair (TR)	<input type="radio"/> Do not use, retire (R)	<input type="radio"/> N/A Not applicable
---	---------------------------------------	--------------------------------------	--	---

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

☒ ☐ ☐ ☐ ☐ N/A

2. Preliminary observations

Verify the presence and legibility of the serial number and the CE mark.
Verify that the product lifetime has not been exceeded.
Compare with a new device to verify there are no modifications or missing elements.

☐ ☐ ☐ ☐ ☐

3. Checking the general condition

- Check the condition of the side plates (marks, deformation, cracks, corrosion, wear...).
- Check the condition of the attachment holes (marks, deformation, cracks, corrosion...).
- For pulleys with moving side plates, verify that the side plates rotate properly.
- Check the condition of the rivets (marks, deformation, cracks, corrosion, absence of play...).

☐ ☐ ☐ ☐ ☐

4. Checking the condition of the sheave

- Check the condition of the sheave (marks, deformation, corrosion, absence of foreign bodies...).
- Verify that the sheave turns freely.

☐ ☐ ☐ ☐ ☐

5. Function check

- Install your pulley on an anchor and install a compatible rope around the sheave.
- Circulate the rope in both directions.

☐ ☐ ☐ ☐ ☐

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

- ☐ Product **fit** to remain in service
- ☐ Product **unfit** to remain in service

Inspected by

Company

Date Next inspection date