



• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.

• PPE inspection should be conducted with the manufacturer's Instructions for Use.

Download the instructions at $\underline{\text{PETZL.COM}}$





ASAP'SOF User information **PPE** information Surname Model Address Serial number Year of manufacture Date of purchase Identifier Date of first use Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France X 0 Q **⊗**▶ 📆 N/A Good condition (G) To monitor (TM) To repair (TR) Do not use, retire (R) Not applicable 1. Known product history Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...): 0 N/A 2. Preliminary observations • Verify the presence and legibility of the serial number and the CE mark. Verify that the product lifetime has not been exceeded. Compare with a new device to verify there are no modifications or missing elements. 3. Preparation • Depending on your model, remove the CAPTIVs, carabiners and STRING, or remove the ASAP'SORBER from the ASAP LOCK. 4. Checking the condition of the energy absorber • Check the condition of the pouch. Look for wear and damage due to use (cuts, fuzziness, signs of chemicals...). Open the pouch and pull out the energy absorber. • Check the condition of the energy absorber. Look for wear and damage due to use (cuts, fuzziness, signs of chemicals...). • Check the condition of the safety stitching on both sides. Look for any threads that are loose, worn, or cut. Verify that the energy absorber has not sustained an impact load (verify that none of the fabric between the straps has been torn). On the ASAP'SORBER international version and ASAP'SORBER AXESS, verify that the fall indicator has not been torn. Check the condition of the connection points. Look for wear and damage due to use (cuts, fuzziness, signs of chemicals...). Put the energy absorber back in the pouch and close it. Verify that all of the energy absorber webbing is properly protected in the pouch. 5. Checking the condition of the connectors • For connector inspection, see the inspection form for your connector model at Petzl.com. 6. Checking the protection elements • Check the condition of the STRINGs. Reinstall the STRINGs on the attachment points. Verify that the connector/sling/STRING assembly is correct. Verify that the STRING correctly positions the connector. Reinstall the connectors. If applicable, reinstall the CAPTIVs on the connectors.

| Comments (detail here any defects found on the product and accomplished tasks) | | | | | |
|--|--------------|--|--|--|--|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| ' | | | | | |
| VERDICT | Inspected by | | | | |

| VERDICT | |
|---------|---|
| | Product fit to remain in service |
| | Product unfit to remain in service |

| Inspected by | | |
|--------------|----------------------|--|
| Company | | |
| Date | Next inspection date | |